

What is claimed is:

1. Washing apparatus comprising

5

- a First Region (1), to which a wash material (4) is supplied,
- a Second Region (2), in which the wash material (4) is washed, and
- a Third Region (3), in which the wash material (4) is melted, and also

10

- a flow resistance (6) provided between the Second Region (2) and the Third Region (3),

wherein the Second Region (2) is at least partially in the form of a column (2a) and wherein this column has a diameter of at least 300 mm.

15

2. Washing apparatus according to claim 1, wherein the flow resistance is arranged non-rotatably about a central longitudinal axis (5) of the Second Region (2).

20

3. Washing apparatus according to claim 1 or 2, wherein there is provided between the First Region (1) and the Second Region (2) a solid/liquid separation apparatus, preferably a filter (7), having a filtrate offtake line (8).

4. Washing apparatus according to claim 3, wherein the solid/liquid separation apparatus is in the form of a filter (7) in a wall (9) adjacent to the Second Region (2).

25

5. Washing apparatus according to claim 4, wherein the wall (9) is arranged at an angle α in the range from > 0 and $< 90^\circ$, relative to the central longitudinal axis (5).

6. Washing apparatus according to any one of the preceding claims, wherein the flow resistance (6) has at least one opening (10).

30

7. Washing apparatus according to any one of the preceding claims, wherein the flow resistance (6) is characterised by a relative free cross-sectional area in the range from > 0 to $< 100\%$, relative to the total area of the flow resistance.
- 5 8. Washing apparatus according to claim 7, wherein the free cross-sectional area is variable.
9. Washing apparatus according to one of claims 7 and 8, wherein the flow resistance (6) can be tempered.
- 10 10. Washing apparatus according to one of the preceding claims, wherein a conveying means (61) free of pulsation is provided upstream of the First Region (1) or at least partially in the First Region.
- 15 11. Washing apparatus according to claim 10, wherein the conveying means (61) free of pulsation has a conveyor spiral (61).
12. Purification apparatus comprising a crystal-producer (13) that is connected in a crystal-carrying way with the First Region (1) of a washing apparatus comprising
20
 - a First Region (1), to which a wash material (4) is supplied,
 - a Second Region (2), in which the wash material (4) is washed, and
 - a Third Region (3), in which the wash material (4) is melted, and also
- 25
 - a flow resistance (6) provided between the Second Region (2) and the Third Region (3),or the washing apparatus defined in one of the preceding claims.
13. Purification apparatus comprising a crystal-producer (13) that is connected in a crystal-carrying way with the First Region (1) of a washing apparatus comprising
30
 - a First Region (1), to which a wash material (4) is supplied,
 - a Second Region (2), in which the wash material (4) is washed, and

- a Third Region (3), in which the wash material (4) is melted, and also
- a flow resistance (6) provided between the Second Region (2) and the Third Region (3).

- 5 14. Purification apparatus according to claim 12 or 13, wherein a dwell-time container (49) is provided between the crystal-producer (13) and the washing apparatus.
15. Synthesis device comprising a synthesis installation (14) and downstream a purification apparatus as defined in one of claims 12 to 14.
- 10 16. Synthesis device according to claim 15, wherein the synthesis installation (14) is a gaseous phase oxidation synthesis unit.
17. Method of purifying a wash material, wherein the wash material is supplied by way of
- 15 the First Region (1) of a washing apparatus defined in one of claims 1 to 11 and a target product is obtained.
18. Method according to claim 17, wherein the wash material contains at least 20 % of the target product by weight.
- 20 19. Use of the target product, obtainable by a method according to claim 17 or 18 in the production of food, polymers, fuels, lubricants, cleaning agents, dyes or pharmaceuticals.
- 25 20. Use of a washing apparatus according to one of claims 1 to 11 or of a purification apparatus according to claim 12 or 13 in the purification of target products such as food, monomers, fuels, solvents; or in waste-water treatment; or in isomer separation.